

Material Safety Data Sheet

FIR No.: 173576
Version Number: US-US-1

Level: 1
Release Date: 2005-07-12

1. Product and Company Identification

Product Name: SAE 80W-90 Premium Rear Axle Lubricant
Product Code: See Attachment
Application: Rear Axle Lubricant
Supplier: Ford Motor Company
 Attention: MSDS Information, P.O. Box 1899
 Dearborn, Michigan 48121
 1-800-392-3673

Emergency Telephone: Poison Control Center: 1-800-959-3673
 CHEMTREC: U.S. and Canada: 1-800-424-9300
 CHEMTREC: International: 1-703-527-3887

2. Composition/Information on Ingredients

This chemical product is a preparation.

Chemical Name	CAS Number	Percent Concentration	Hazard Classification
PETROLEUM DISTILLATES HYDROTREATED HEAVY PARAFFINIC	64742-54-7	50-70	HAZCOM RSMSPROH
RESIDUAL OILS (PETROLEUM), SOLVENT REFINED	64742-01-4	20-40	HAZCOM RSMSPROH
PETROLEUM DISTILLATES, SOLVENT DEWAXED LIGHT PARAFFINIC	64742-56-9	1-5	HAZCOM RSMSPROH
SULFURIZED ISOBUTYLENE	68511-50-2	1-5	

3. Hazards Identification

Health: This product may cause mild irritation to the eyes and skin.

Environment: Material contains a chemical which is a Hazardous Air Pollutant (HAP), regulated by the United States Clean Air Act.

4. First-Aid Measures

Inhalation: If gas/fume/vapor/dust/mist from the material is inhaled, remove the affected person immediately to fresh air. If irritation persists, get medical attention.

Skin Contact: Wash skin with soap and water. If irritation persists, get medical attention.

Eye Contact: In case of contact with eyes, rinse immediately with plenty of water for at least 15 minutes and seek medical attention.



Material Safety Data Sheet

FIR No.: 173576
Version Number: US-US-1

Level: 1
Release Date: 2005-07-12

Ingestion: First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

Notes to a Physician: HIGH PRESSURE SKIN INJECTION: Physician must be familiar with local procedures for treatment of this type of wound; incision, irrigation, removal of all necrotic tissue and open wound dressing. This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately. If the affected person is not breathing, apply artificial respiration. If the affected person's breathing is difficult, give oxygen.

5. Fire-Fighting Measures

Extinguishing Media: Dry chemical, foam, carbon dioxide, water fog.

Specific Methods: Use water to cool fire-exposed containers, structures, and to protect personnel. Use water to dilute spills and to disperse flammable vapors.

Specific Hazards: Due to pressure buildup, closed containers exposed to excess heat may explode. Empty container(s) may retain product residue -- solid, liquid, and/or vapor -- and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Water or foam may cause frothing if the product is heated above 93 degrees C (200 degrees F).

Protection of Firefighters: Fire fighters should be equipped with NIOSH-approved, self-contained breathing apparatus (SCBA) and full protective clothing.

6. Accidental Release Measures

Personal Precautions: Avoid excessive skin contact with the spilled material. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material. Wear appropriate protective equipment and clothing during clean-up.

Environmental Precautions: Do not allow the spilled product to enter public drainage system or open water courses.

Methods for Cleaning Up: Absorb the spilled material with an inert absorbent (nonflammable) material. Dike the spilled material, where this is possible. Stop the flow of material, if this is without risk.



Material Safety Data Sheet

FIR No.: 173576
Version Number: US-US-1

Level: 1
Release Date: 2005-07-12

7. Handling and Storage

Handling:

Technical Measures: Avoid the generation of oil mists.

Precautions and Advice for Safe Handling: Avoid contact with skin, eyes and clothing.
Avoid prolonged or repeated skin contact with this material.
Elevated temperature or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, and lungs.
Avoid breathing vapors or mist.
Eliminate all sources of ignition.

Storage:

Technical Measures: No special precautions necessary.

Storage Conditions: Keep the container tightly closed and dry.
Keep this product from heat, sparks, or open flame.
Store this product away from strong oxidizing agents.
Store this product in a cool, dry, well-ventilated place.

8. Exposure Controls/Personal Protection

Engineering Measures: Use general ventilation.
Eyewash and emergency showers are recommended.

Control Parameters: If oil mist is generated, observe the OSHA exposure limit of 5 mg/m3.
Ford Motor Company recommends an exposure limit of 1.0 mg/m3.

Personal Protective Equipment:

Respiratory Protection: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.

Hand Protection: Use of impervious gloves is recommended, such as neoprene.

Eye Protection: Wear safety glasses with side shields.

Skin and Body Protection: Remove contaminated clothing and wash before reuse.

Hygiene Measures: Wash thoroughly after handling.



Material Safety Data Sheet

FIR No.: 173576
Version Number: US-US-1

Level: 1
Release Date: 2005-07-12

9. Physical and Chemical Properties

Specific Gravity: 0.88-0.89
Physical State: LIQUID
Odor: PETROLEUM
Color: AMBER
pH: N.AV
Temperature Range During which Changes in Physical State Occur:
Flash Point: 150 minimum °C ASTM D93
Auto-ignition Temperature: N.AV
Explosion Properties:
 UEL: N.AV
 LEL: N.AV
Vapor Pressure: <1@20°C mmHg
Vapor Density: >1 (AIR=1)
Solubility: NEGLIGIBLE IN WATER
Viscosity: 131-152@40°C cSt ASTM D445
Evaporation Rate: <1 (BuAc = 1)

10. Stability and Reactivity

Stability: This is a stable material.
 Hazardous polymerization will not occur.

Conditions and Materials to Avoid: This product may react with oxidizing agents.
 This product may react with reducing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other low molecular weight hydrocarbons.
 Decomposition of this product may yield oxides of phosphorus.
 Decomposition of this product may yield oxides of sulfur and nitrogen.

11. Toxicological Information

Skin Contact: Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Chronic (Long Term) Toxicity: Base oil severely refined: Not carcinogenic in animal studies.
 Representative material passes IP-346, Modified Ames test, and/or other screening tests.



Material Safety Data Sheet

FIR No.: 173576
Version Number: US-US-1

Level: 1
Release Date: 2005-07-12

12. Ecological Information

No specific aquatic data available for this product.

13. Disposal Considerations

Waste from Residues:

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulation.
Empty containers may contain hazardous residues (vapors, liquid, and/or solid). Do not reuse the empty container without commercial cleaning or reconditioning.

Contaminated Packaging:

No available information.



Material Safety Data Sheet

FIR No.: 173576
Version Number: US-US-1

Level: 1
Release Date: 2005-07-12

14. Transport Information

U.S. Department of Transportation (DOT) 49 - CFR 172.101

This product is not regulated as a dangerous good.

Canadian Transportation of Dangerous Goods (T.D.G.) - TDGR Schedule II

This product is not regulated as a dangerous good.

Secretary of Communication and Transportation (SCT) - NOM-002-SCT2/1994 (Mexico)

This product is not regulated as a dangerous good.

International and Domestic Air Transportation - ICAO & IATA Section 4.2

This product is not regulated as a dangerous good.

International Water Transportation - IMDG Code Amendment 31-02

This product is not regulated as a dangerous good.

15. Regulatory Information

The components of this product are listed on the TSCA Inventory

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372

Used engine oils, while not a component of this material, is on the Proposition 65 list of chemicals known to the State of California to cause cancer.

Material contains a chemical which is a Ford Motor Company Material of Concern. Use and release of this material should be minimized to the greatest extent possible.

16. Other Information



Key/Legend: N.AP = Not applicable; N.AV = not available; ND = Not determined or No data; TLV = Threshold limit value; TWA = Time-weighted average; STEL = Short-term exposure limit; C = Ceiling limit

Preparation Information:

The chemical identification and properties for this material were provided by the manufacturer. For Canadian locations, a manufacturer's MSDS is available upon request. Health and safety information has been evaluated by the Occupational and Environmental Health Sciences Department, Ford Motor Company, National Parts General Office, MD74, 29500 Plymouth Road, Livonia, MI 48150, USA.

Disclaimer:

The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.



Material Safety Data Sheet

FIR No.: 173576
Version Number: US-US-1

Level: 1
Release Date: 2005-07-12

Attachment

Product Code	Container Size	Part of Kit	Kit Product Code
XY-80W90-KL	16 U.S. gal		
XY-80W90-QL	1 qt		