



Dilmar Oil Company

Multi Vehicle Synthetic Blend Automatic Transmission Fluid

Automatic Transmission Fluid

Product Description

Multi-Vehicle Synthetic Blend Automatic Transmission Fluid is a premium quality, semi-synthetic transmission fluid designed for use in automatic transmissions in most domestic and import passenger cars and light trucks. This fluid has been formulated to provide smooth shifting and excellent anti-shudder performance in a wide variety of vehicles. It has exceptional shear stability and oxidization resistance of long service life, providing excellent wear protection, and helps protect against sludge and varnish buildup.

Approved for: ZF application TE ML 03D, 04D, 14B, 16L, and 17C. Voith Transmissions (approval 3 H-36366)

Recommended for service fill for GM Dexron® III-H, Allison C-4, Ford Mercon® and Mercon® V, Chrysler (ATF +3 and +4), Honda/Acura, Hyundai, Jeep, Mercedes-Benz, Mitsubishi (Diamond SP II or SP III), Nissan, (Matic D, J or K)/Infiniti, Saturn, Toyota (T-III & T-IV)/Lexus/Scion, VW/Audi, most European vehicles including BMW & Volvo, most Asian vehicles including Daewoo, Isuzu, Kia, Mazda and Suzuki.

Multi-Vehicle Synthetic Blend Automatic Transmission Fluid is not for use in transmissions requiring Ford Type F or DEXRONVI, or in Continuously Variable Transmissions (CVT) applications.

Characteristics

| | <u>Typical</u> |
|-----------------------|-----------------------|
| Gravity, API | 33.20 |
| Density, lbs/gals | 7.14 |
| Viscosity @ 40°C, cSt | 34.90 |
| Viscosity Index | 210 |
| Color | Red |

Approvals

Ford Mercon® V License
Ford Mercon® License
Voith
Allison C-4
ZF

Numbers

M5041201
M041209
H-36366
C4-31062006
TE-ML, 03D, 04D, 14B, 16L, 17C