



Dilmar Oil Company

1951 W. Darlington Street, Florence SC 29501
1-800-922-5823

Universal Tractor Fluid

Dilmar **Universal Tractor Fluid** is a premium lubricant for farm and construction type wheeled tractors that are typically designed to use a common fluid to lubricate the transmission, differential, PTO and hydraulic systems. The fluid successfully meets the special lubricity and wear protection requirements of the gear sets and hydraulic system components as well as provide the special friction needs of wet brakes and clutches that may be used on the equipment.

Dilmar Universal Tractor Fluid meets or exceeds the specifications of:

Allison C-3, C-4	Deutz-Allis 272843	New Holland FNHA-2-C-200/201
Allis Chalmers 272843	Ford M2C41-B and M2C134-D	Oliver Type 55
J.I. Case MS-1206, 1210	Hesston-Fiat AF-87	Renk 874 A/B Transmissions
Caterpillar TO-2	International Harvester B-6	Steiger HTF (SEMS 17001)
Clark transmissions	Kubota UDT Fluid	Sauer-Sunstrand Pumps
John Deere J20C, J21A, J14C, JD 303 Massey Ferguson MF 1135/1141	White Q-1826 and Type 55	

Typical Properties:

SAE Grade	<u>10w-20</u>
API Gravity @ 60' F	30.8
Viscosity, cSt	
40° C	59.0
100° C	9.20
Viscosity Index, minimum	133
Flash Point, ° F	400+
Pour Point, ° F	-40