

## All-Season Utility Hydraulic Fluid

### DESCRIPTION

All-Season Utility Hydraulic Fluid is formulated from select base stocks and a robust additive system for use as a multi-purpose lubricant for industrial machinery, farming, off-highway construction and logging equipment in final drives, wet brakes, power steering units and hydraulic systems. It delivers reliable component durability and system performance.

### PERFORMANCE BENEFITS

- Robust extreme pressure (EP) and anti-wear additives protect critical system components
- Special detergents reduce sludge and deposit formation, maintaining system cleanliness
- Balanced frictional properties deliver smooth clutch and PTO operation
- Outstanding resistance to rust, corrosion and oxidation
- Excellent anti-shudder performance
- Multi-functional lubricant performance

### PRODUCT APPLICATION

Utility Hydraulic Fluid is specifically designed for equipment manufactured before 1989 or where frequent fluid replacement is required.

Recommended for use in ambient temperatures between 0°F and 122°F (-18°C to 50°C)

Typical Physical Properties		
Property	Method	
SAE Grade	J-300	20
Viscosity, cSt @ 40°C	D-445	49.5
Viscosity, cSt @ 100°C	D-445	7.5
Viscosity Index	D-2270	125
Specific Gravity @ 60°F	D-1250	0.865
Flash Point, COC, °C(°F)	D-92	221 (430)
Pour Point, °C(°F)	D-97	-48 (-54)
Color	D-1500	3.5
Minor variations in physical test results may occur in the course of normal manufacturing		

**Always consult original equipment manufacturer lubricant recommendation for proper fluid application. Fluid misapplication in late model equipment may cause significant damage.**

**MANUFACTURED EXCLUSIVELY IN THE U.S.A.**