

Synmax Synthetic Motor Oils -

All Grades

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Dilmar Synmax Synthetic Motor Oil – All Grades

Part Number: synmax0w20-55; synmax0w20-b

synmax1030-55; synmax1030-b synmax5w20-55; synmax5w20-b synmax530-b; synmax530-55

Distributor: Dilmar Oil Co., Inc. 1951 W. Darlington St. Florence, SC 29501 800-922-5823

Emergency Phone Number: During normal business hours – 800-922-5823

Recommend Uses: Engine oil formulated for turbo-charged and naturally spirited gasoline, propane, natural gas engines

in passenger car and light duty truck service.

SECTION 2. HAZARD(S) IDENTIFICATIONS

Emergency Overview

Appearance	Liquid
Color	Amber
Odor	Mild

GHS Classification:

Not a hazardous substance or mixture.

GHS Label Elements:

Not a hazardous substance or mixture.

Potential Health Effects

Primary Routes of Entry: Eye contact

Ingestion Inhalation Skin contact

Aggravated Medical Condition: None Known

Other hazards which do not result in classification

No Data Available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture: Mixture

Hazardous component(s)

Chemical NameCAS-No.Concentration (%)Highly refined mineral oilMixture80 – 90 %weightPetroleum AdditivesMixture10 – 20 %weight

SECTION 4. FIRST-AID MEASURES

If inhaled: Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact:

In case of contact, immediately flush eyes or skin with plenty of water for at

least 15 minutes while removing contaminated clothing and shoes.

Safety Data Sheet



Wash skin thoroughly with soap and water or use recognized skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact: Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes.

Obtain medical attention.

If swallowed: Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physician or poison

control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms

and effects, both acute and delayed: First aider needs to protect himself.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Product will float and can be reignited on surface of water.

Unsuitable extinguishing media: Do not use a direct stream of water.

Specific hazards during firefighting: Cool closed containers exposed to fire with water spray.

Hazardous combustion products: No information available.

Further information: Prevent fire extinguishing water from contaminating surface water or the

ground water system. Recommend wearing self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, Use personal protective equipment.

Protective equipment and Ensure adequate ventilation. Emergency procedures: Evacuate personnel to safe areas.

Material can create slippery conditions.

Environmental precautions: If the product contaminates rivers and lakes or drains inform

Respective authorities.

Methods and materials for Prevent further leakage or spillage if safe to do so.

containment and cleaning up: Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation.

Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling: For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application area. In case of insufficient ventilation, wear suitable respiratory equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition.



Keep container closed when not in use.

Conditions for safe storage: Store in original container.

Containers which are opened must be carefully resealed and kept upright to

prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not use in heat or direct sunlight.

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures: No special ventilation requirements. Good general ventilation should be

sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Respiratory protection: Use respiratory protection unless adequate local exhaust ventilation is

provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Filter type: Organic vapor filter

Hand protection material: Neoprene, Nitrile, Polyvinyl Alcohol (PVA), Viton(R).

Remarks: Chemical-resistant, impervious gloves complying with an approved standard

should be worn at all times when handling chemical products if a risk

assessment indicates this is necessary.

Eye protection: Wear safety glasses or face-shield and protective suit for abnormal

processing problems.

Skin and body protection: Choose body protection in relation to its type, to the concentration and

amount of dangerous substances, and to the specific work-place.

Protective measures: Wash hands and face before breaks and immediately after handling the product.

Wash contaminated clothing before re-use.

Ensure that eyewash station and safety shower are proximal to the work-station

location.

Hygiene measures: Remove and wash contaminated clothing and gloves, including the inside,

before re-use.

Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid
Color: Amber
Odor: Mild

Odor Threshold:

pH:

No data available

No data available

Pour point:

<-38 °C, -36.4 °F

Melting point/freezing point:

No data available

Boiling point/boiling range:

289 °C, 552 °F (Initial)

Flash Point: 205 °C, 401 °F

200 °C, 392 °F*

*0W20



Fire Point: No data available No data available Auto-Ignition Temperature: Decomposition Temperature: No data available No data available **Evaporation Rate:** Flammability: No data available Upper explosion limit: No data available Lower explosion limit: No data available Vapor pressure: No data available

Relative vapor density: > 1 (air=1)

Density: No data available

Solubility (ies):

Water solubility: Insoluble

Partition coefficient: n- No data available.

Octanol/water

Viscosity

Viscosity, Kinematic: $(100 \,^{\circ}\text{C}) \, 5.6 \, \text{cSt} - 9.0 \, \text{cSt}^*$

(100 °C) 9.3 cSt – 12.5 cSt** (100 °C) 5.6 cSt – 9.2 cSt***

*0W20, **5W30 & 10W30 , ***5W20

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions: Hazardous polymerization does not occur.

Stable under normal conditions.

Conditions to avoid: No data available

Incompatible materials: Reactive with oxidizing agents, acids, alkalis and reducing agents.

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product:

Acute oral toxicity Remarks: No data available Remarks: No data available Remarks: No data available Remarks: No data available

Skin corrosion/irritation

Product:

Remarks: No data Available

Serious eye damage/eye irritation

Product:

Remarks: No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available



Carcinogenicity

Product:

Remarks: Not expected to be carcinogenic.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skin painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

IARC No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

ACGIHNo component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by ACGIH.

OSHANo component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity Product:

Toxicity to fish: Remarks: No data available Toxicity to daphnia and other: Remarks: No data available

aquatic invertebrates

Toxicity to algae: Remarks: No data available Toxicity to bacteria: Remarks: No data available

Persistence and degradability

Product:

Biodegradability: Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues: The product should not be allowed to enter drains, water courses or the

soil.

Offer surplus and non-recyclable solutions to a licensed disposal company.

Waste must be classified and labelled prior to recycling or disposal.

Send to a licensed waste management company.



Dispose of as hazardous waste in compliance with local and national

regulations.

Dispose of product residue in accordance with the instructions of the person

responsible for waste disposal.

Contaminated packaging: Do not re-use empty containers.

SECTION 14. TRANSPORTATION INFORMATION

International Regulation

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

49 CFR

Not regulated as a dangerous good

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

OSHA Hazards:No data available

Clean Water Act (CWA) 307: zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis (phosphorodithioate); Zinc alkyl

dithiophosphate

Clean Water Act (CWA) 311: vinyl acetate

This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800)424-8802.

Composition/information on ingredients

		SARA 302 TPQ	SARA 304 RQ
Name	% EHS	(lbs) (gallons)	(lbs) (gallons)
Vinyl acetate	<0.01 yes	1000 140	5000 666.8
SARA 311/312			644.8*

Classification Not applicable

*0W20

The components of this product are reported in the following inventories:

DSL No data available

TSCA All components are listed or exempted.

IECSC Not determined.


EINECS At least one component is not listed in EINECS but all such components

are listed in ELINCS.



SECTION 16. OTHER INFORMATION

Further information NFPA:



HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Guide to Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection Agency; GHS = Globally Harmonized System; IARC = International Agency for Research on Cancer; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

Prepared by: Dilmar Oil Co., Inc.

Revision date: 06/2015

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.