



## All-Season Hydraulic AW Oil

### DESCRIPTION

**All-Season Hydraulic AW Oils** are multi-purpose, hydraulic, industrial lubricants formulated from premium base stocks and a robust additive system to deliver reliable equipment protection in non-critical applications.

All-Season Hydraulic AW Oil contains anti-wear agents to minimize component deterioration in vane, gear and piston type hydraulic pumps. It is available in multiple viscosity grades to meet a wide-variety of general-purpose lubrication and hydraulic applications.

### PERFORMANCE BENEFITS

- Anti-wear additives protect critical system components
- Added resistance to rust and oxidation
- Excellent anti-foam performance
- Emulsifies (mixes) with moisture in hydraulic and circulating systems
- Delivers smooth hydraulic operation through rapid air release
- Outstanding general-purpose lubricant for non-critical applications

### PRODUCT APPLICATION

All-Season Hydraulic AW Oils are recommended for:

- Non-critical hydraulic systems
- Low-pressure circulating systems
- General-purpose machine oil
- Log splitters
- Drip or splash lubrication of non-critical gears

Typical Physical Properties				
Property	Method			
ISO Grade		32	46	68
Viscosity, cSt @40°C	D-445	34.8	48.6	64.5
Viscosity, cSt @100°C	D-445	6.8	7.0	7.8
Viscosity Index	D-2270	105	105	105
Specific Gravity, @60°F	D-1250	0.865	0.870	0.875
Flash Point, COC, °C(°F)	D-92	213 (415)	218 (425)	229 (445)
Pour Point, °C(°F)	D-97	-37 (-35)	-32 (-25)	-30 (-22)
ASTM Color	D-1500	1.5	2.5	3.5
Minor variations in physical test results may occur in the course of normal manufacturing				

**Always consult original equipment manufacturer lubricant recommendation for proper fluid application. Fluid misapplication may cause significant damage.**

**MANUFACTURED EXCLUSIVELY IN THE U.S.A.**