



Dilmar Oil Company

Grease 0886 #2.5

Dilmar Grease 0886 # 2.5 is an outstanding multipurpose, extreme pressure (EP) Lithium Hydroxy grease. This product is recommended for extended service in heavy duty automotive, trucks, buses, farm tractors and construction equipment. The low bleed characteristic is particularly used in poorly sealed bearings. Dilmar Grease 0886 # 2.5 can also be used in lubricating many types of industrial machinery where poly-lithium-EP grease specified.

Qualities:

- Fully refined lube stocks are combined with a high quality lithium soap and additives under rigid laboratory and process control. Special compounding supplies beneficial anti-friction properties.
- Resists thinning or hardening in bearings, thereby minimizing leakage and maintaining lubrication in long-life service.
- It effectively resists washout and excessive dilution by water, assuring all-weather lubrication.
- Offers excellent low temperature pump ability and high temperature protection.

APPLICATIONS

Is high recommended for chassis, universal joint, equipment, and automobiles. Its multipurpose capability usually eliminates the need for other greases, thus avoiding the danger of misapplication or mixing greases of difference base types.

TYPICAL PROPERTIES	
Viscosity cSt @ 40 °C	182
Viscosity cSt @ 100 °C	15.4
Viscosity SUS @ 100 °F	963
Viscosity SUS @ 210 °F	81
Worked Penetration	280
Dropping Point, °F	360
Soap Type	Lithium-12 Hydroxy
Soap, %	7-11
Timken, OK Load, Lbs.	45