



# Dilmar Oil Company

## Hi Mileage SAE 10W30 Motor Oil

Dilmar Hi Mileage SAE 10W30 motor oil is specially formulated from a proprietary combination of select base stocks and an additive technology that delivers ultimate protection to mature vehicles with 75,000 miles or more on the odometer. This additive system contains active cleaning agents that maintain performance in older engines. Dilmar Hi Mileage SAE 10W30 is also formulated with special seal conditioners that recondition and revitalize brittle, cracked or worn-out O-rings, gaskets and seals in older vehicles, reducing oil consumption, driveway leaks and minimizes exhaust smoke.

VEHICLE BENEFITS	PRODUCT FEATURES
<ul style="list-style-type: none"><li>• Superior wear protection for older engines</li><li>• Protects against oil burn-off and consumption between services</li><li>• Maximum resistance to high-temperature thermal breakdown</li></ul>	<ul style="list-style-type: none"><li>• Exceeds ILSAC standards GF-5 and API classification Resource Conserving SN</li><li>• Proprietary base stock formulation provides resistance to thermal breakdown</li><li>• Additive technology that maintains mature engine cleanliness and resists sludge and piston deposits</li></ul>

### APPLICATIONS

Recommended for turbo-charged or naturally aspirated gasoline-powered passenger cars, light trucks and sport utility vehicles with 75,000 odometer miles or more:

- ILSAC standards GF-5 and API classification Resource Conserving SN
- Backward compatible for API classifications SJ, SL, & SM to deliver ultimate mature engine protection

TYPICAL PROPERTIES		
GRADE	TEST METHOD	10W30
ILSAC/API Service		GF-5/SN
Flash Point °C (°F)		224 (435)
Density @ 15 °C, g/cc <sup>3</sup>	ASTM D4052	0.875
Viscosity cSt @ 40 °C	ASTM D445	70.7
Viscosity cSt @ 100 °C	ASTM D445	10.5
Viscosity Index	ASTM D2270	138
TBN, mg KOH	ASTM D2896	8.5
Sulfated Ash, wt. %	ASTM D4951	0.93
Zinc, wt %	ASTM D4951	0.098