

Polystar EP # 00 Grease

Dilmar Polystar EP # 00 is a premium, extreme pressure, multi-purpose, long life grease, which exhibits excellent thermal stability, excellent high and low temperature capabilities and superior shear stability when compared to typical polyurea greases. This grease has excellent water resistance characteristics and will not washout. It maintains its consistency under severe working conditions, and resists rust and oxidation.

Dilmar Polystar EP # 00 is recommended for sealed for life bearings, rolling element bearings and other range of industrial applications. This grease is recommended in any application where high temperatures and heavy load conditions prevails.

| <u>Features</u> | | <u>Benefits</u> | |
|-----------------|---|-----------------|---|
| • | Excellent Extreme Pressure properties | • | Works under severe, heavy and shock load conditions |
| • | Very good oxidation and rust protection | • | Extended service under at high temperatures |
| • | Outstanding High Temperature properties | • | Provides effective lubrication for extended period of time and at high temperatures |
| • | Good water resistance | • | Does not washout under water ingress conditions |

| Product Number | PO00B | Test Method |
|-------------------------------|----------------------|-------------|
| Color | Green | Visual |
| Texture | Smooth , homogeneous | Visual |
| Thickener Type | Polyurea | |
| NLGI Grade | 2 | ASTM D 217 |
| Worked Penetration | 265-295 | ASTM D 217 |
| Drop Point , ⁰ F | 500 Min. | ASTM D 2265 |
| Viscosity @ 40 C ,cSt | 145 | ASTM D 445 |
| Weld load, kg | 500 min | ASTM D 2596 |
| Timken OK load , lbs | 60 | ASTM D 2509 |
| Rust Test | Pass | ASTM D 1743 |
| Water Washout , 175 F , % wt. | 5.0 % Max. | ASTM D 1264 |
| Water Spray off, % wt | 20 max. | ASTM D 4049 |

04/2015